







# ENT Accessories Features and Benefits

## TRANSITION ADAPTERS

 <b>Features</b>	<b>ENT to EMT Transition Adapters</b> Part Numbers: A245D, A245E, A245F <b>Benefits</b> 
<ul style="list-style-type: none"> <li>• <b>Nonmetallic, Noncorrosive, Nonconductive</b></li> </ul>	<ul style="list-style-type: none"> <li>• Extends product life, eliminates rust and the need for replacement, and provides safe handling/installation.</li> <li>• Lightweight</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Concrete Tight</b></li> </ul>	<ul style="list-style-type: none"> <li>• Able to withstand the harsh environments of concrete construction.</li> <li>• Designed specifically for poured concrete slab applications.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Flexible</b></li> </ul>	<ul style="list-style-type: none"> <li>• Provides an easy transition from Carlon ENT to an EMT conduit system.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Carlon "Quick Connect" Snap-In Design</b></li> </ul>	<ul style="list-style-type: none"> <li>• Provides a secure, fast, easy installation.</li> <li>• The reinforcement screw prevents the EMT from slipping/shifting.</li> <li>• Saves time and money.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Eliminates off-site Modifications</b></li> </ul>	<ul style="list-style-type: none"> <li>• Saves time and money.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Manufactured from Polycarbonate Material</b></li> </ul>	<ul style="list-style-type: none"> <li>• Designed to out perform today's competitive ENT products by providing better structural integrity &amp; a higher resistance to the environmental extremes of concrete construction.</li> <li>• Rugged and Durable.</li> <li>• Will not crush/collapse under the tremendous weight of concrete installations.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Variety of Sizes</b></li> </ul>	<ul style="list-style-type: none"> <li>• Available in sizes 1/2", 3/4" and 1" to accommodate any jobsite requirement.</li> </ul>



 <b>Features</b>	<b>ENT Reducers</b> Part Numbers: A273DE, A273EF <i>(Patent Pending)</i> <b>Benefits</b> 
<ul style="list-style-type: none"> <li>• <b>Nonmetallic, Noncorrosive, Nonconductive</b></li> </ul>	<ul style="list-style-type: none"> <li>• Extends product life, eliminates rust and the need for replacement, and provides safe handling/installation.</li> <li>• Lightweight</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Concrete Tight</b></li> </ul>	<ul style="list-style-type: none"> <li>• Able to withstand the harsh environments of concrete construction.</li> <li>• Designed specifically for poured concrete slab applications. No need to tape.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Flexible</b></li> </ul>	<ul style="list-style-type: none"> <li>• Provides an easy transition from one Carlon ENT size to another.</li> <li>• Minimize the need to carry size specific boxes and fittings.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Carlon "Quick Connect" Snap-In Design</b></li> </ul>	<ul style="list-style-type: none"> <li>• Provides a secure, fast, easy installation.</li> <li>• <b>NO TAPING REQUIRED.</b></li> <li>• Saves time and money.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Eliminates off-site Modifications</b></li> </ul>	<ul style="list-style-type: none"> <li>• Saves time and money.</li> <li>• Correct jobsite alterations immediately.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Manufactured from Polycarbonate Material</b></li> </ul>	<ul style="list-style-type: none"> <li>• Designed to out perform today's competitive ENT products by providing better structural integrity &amp; a higher resistance to the environmental extremes of concrete construction.</li> <li>• Rugged and Durable.</li> <li>• Will not crush/collapse under the tremendous weight of concrete installations.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Variety of Sizes</b></li> </ul>	<ul style="list-style-type: none"> <li>• Available in sizes 3/4" to 1/2", and 1" to 3/4" to accommodate any jobsite requirement.</li> </ul>