

PRODUCT SPECIFICATIONS

Size	Nom. I.D.	Nom. O.D.	Pull Tape	Min. Bend Radius	Max Flame Rating	Storage	Handling	Wt./ 100 ft. (lbs.)
3/4"	.83"	1.05"	Empty	6"	UL 1666	-4°F – 158°F	-4°F – 104°F	9
1"	1.03"	1.315"	900lb	6"	UL 1666	-4°F – 158°F	-4°F – 104°F	14
1 1/4"	1.38"	1.66"	900lb	7"	UL 1666	-4°F – 158°F	-4°F – 104°F	17
1 1/2"	1.57"	1.90"	900lb	8 1/4"	UL 1666	-4°F – 158°F	-4°F – 104°F	22
2"	2.02"	2.375"	900lb	9 1/2"	UL 1666	-4°F – 158°F	-4°F – 104°F	26

RISER-GARD PART NUMBER SYSTEM

Product	Size	Configuration	Wall	Color	Pull Line	Length
D = Riser-Gard	E = 3/4"	4 = Corrugated	X = Standard	1 = Orange	C = 900 lb. Pull Tape	Example: -1000 = 1000 Feet
	F = 1"			3 = Gray		-1000S = 1000 Feet Split
	G = 1 1/4"			4 = White		
	H = 1 1/2"			7 = Yellow		
	J = 2"					

Note: Custom runs available in minimum order quantities of 1000 feet. Custom orders are NOT returnable.

1 1/2" through 2" sizes of Riser Gard / Optic Gard are suitable for direct burial and plowing applications.

Riser-Gard sizes 3/4" – 1" are acceptable for FT4 applications.

- For use per Articles 770 and 800 of the NEC
- UL Listed to UL1666
- Outside Diameters meet IPS dimensions
- Available in standard or split configurations